

We help you shine.

PE200BU ELECTRIC BURNISHER

## PE200BU ELECTRIC BURNISHER

Non-conductive, commercial grade switch housing.
 Toggle flip adjustable handle for easy operation.
 Full pad-to-floor contact with no compensating castor.
 Flexible pad driver.
 Dual lever on/off safety switch for left or right hand operation.
 5" (13 cm) non-marking, self-lubricating operating wheels.
 7 4" (10 cm) non-marking, self-lubricating transport wheels.
 3 75 ft. (23 m) 12/3 cord for maximum maneuverability.
 No slip, deep V-belt drive transmission.
 1.5 HP D.C. rectified motor .

## Solid and durable

Rugged construction
All metal construction.

## **High performance**

1500 rpm

Available for 110V power supply.

shine on.



Dimensions and Performance Specifications						
Operating Width	Performance	Pad Size	Pad Speed	Power Supply	Noise Level	Weight
20″ (51 cm)	15,000 ft <sup>2</sup> /hr (1380 m <sup>2</sup> /hr)	20″ (51 cm)	1500 RPM	110V	62 dB (A)	101 lb (46 kg)



PowerPolish<sup>™</sup> & PowerPolish HT<sup>™</sup> pads are ideal for curing PowerStar<sup>®</sup> Top Shield coating on concrete surfaces.



EnviroStar Green<sup>®</sup> floor coatings for all types of floor surfaces are effective environmentally preferred chemicals.



Blue Blend<sup>™</sup> and Thermal Thunder<sup>™</sup> pads remove scuffs and scratches for a brilliant wet look shine.



White Lightning<sup>™</sup> curing pads provide optimum appearance on soft or fresh coatings.



© 2012 Amano Pioneer Eclipse Corporation® • 1 Eclipse Road • PO Box 909 • Sparta, NC 28675 USA 1-800-367-3550 • 1-336-372-8080 • Fax: 1-336-372-2895 • www.pioneer-eclipse.com